

CAC

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Patentee: Bohumil Lojek PATENT  
Serial No.: 10/639,073 Group Art: 2818  
Filed: August 11, 2003 Examiner: Andy Huynh  
U.S. Patent: 6,933,557 B2  
Granted: August 23, 2005  
For: FOWLER-NORDHEIM BLOCK ALTERABLE  
EEPROM MEMORY CELL

Request for Certificate of Correction  
of U.S. Patent No. 6,933,557 B2  
for PTO Mistake (37 CFR § 1.322(a))

Commissioner for Patents  
P.O. Box 1450  
Alexandria, Virginia 22313-1450

**Certificate**  
NOV 09 2006  
**of Correction**

Sir:

The following errors appear in the above-identified patent and are of such a nature as to justify the issuance of a Certificate of Correction.

In the Specification

Column 4 at line 39, in accordance with entered amendment dated August 27, 2004, a new paragraph was entered to read as follows:

---With reference to Fig. 3B, the appropriate voltages for reading, erasing, and programming the blocks of the memory array 300 are managed by a memory subsystem 330. As is known to a skilled artisan, a memory controller 340 receives memory subsystem instructions and/or control signals for programming, reading, or erasing blocks or bits of a memory device such as the memory array 300. Additionally, an input/output port 350 (I/O port) receives addresses and provides appropriate voltage levels for word line, bit line, and input/output

NOV - 9 2006

data line selection in support of memory access operations. The I/O port 350 also provides connections for communicating data with the remainder of the system 360. By selecting word lines, bit lines, and source lines and applying appropriate voltages, the controller 340 and I/O port 350 will produce reading, erasing, and programming operations.---

According to entered amendment dated August 27, 2004 the following paragraphs at Column 4, line 52 to Column 5, line 14, identified below, should have been replaced.

"With reference to FIG. 4B, a cross sectional view 400 of the memory cell 310 is illustrated. The memory cell 400 is formed on a semiconductor substrate (or well) 401 of a first conductivity type, which in the exemplary embodiment is p-type. A drain implant region 402 and a source implant region 406, are implanted within an uppermost surface of the substrate 401. A buried, heavily doped implant 404 for the floating gate region is also formed within an uppermost surface of the substrate 401. The implant regions 402, 404, and 406 are of a second conductivity type of a polarity opposite that of the conductivity type of the substrate 401. In a specific exemplary embodiment, the implants are n-type. The buried implant 404 is of n+ conductivity and serves as a tunneling charge source for a floating gate of the memory transistor 400. The drain implant region 402 and the buried implant 404 are spaced apart, so as to define an active region 414 therebetween. Accordingly, the drain implant region 402 connects to the bitline  $BL_i$ . The source implant region 406 connects to the source line  $S_i$ .

A first poly layer 410, forming the floating gate of the memory transistor 304, overlays the buried implant region 404, separated therefrom by a gate ONO

layer 450. A second poly layer 408, forming a common control gate, extends continuously over the first poly layer 410 (which forms the floating gate) from the source dopant region 406 to the drain dopant region 402, overlaying both the buried implant 404 and the select transistor 302 active region 414. A tunnel oxide 460 of thickness 50-70 angstroms is formed in a tunnel window region between the buried implant 404 and the floating gate 410B."

At column 4, line 52 to Column 5, line 13, the aforementioned paragraphs should have been replaced with the following paragraph.

---With reference to FIG. 4B, a cross sectional view 400 of the memory cell 310 is illustrated. The memory cell 400 is formed on a semiconductor substrate (or well) 401 of a first conductivity type, which in the exemplary embodiment is p-type. A drain implant region 402 and a source implant region 406 are implanted within an uppermost surface of the substrate 401. A buried, heavily doped implant 404 within a portion of the floating gate region is formed essentially contiguous with the source implant region 406 within the uppermost surface of the substrate 401. The implant regions 402, 404, and 406 are of a second conductivity type of a polarity opposite that of the conductivity type of the substrate 401. In a specific exemplary embodiment, the implants are n-type. The buried implant 404 is of n+ conductivity and serves as a tunneling charge source for a floating gate of the memory transistor 400. The drain implant region 402 and the buried implant 404 are spaced apart, so as to define an active region 414 in a portion of the space therebetween. Accordingly, the drain implant region 402 connects to the bitline  $BL_1$ . The source implant region 406 connects to the source line  $S_1$ .

NOV - 9 2006

A first poly layer 410, forming the floating gate of the memory transistor 304, overlays the buried implant region 404, separated therefrom by a gate ONO layer 450. A second poly layer 408, forming a common control gate, extends continuously over the first poly layer 410 (which forms the floating gate) from the source dopant region 406 to the drain dopant region 402, overlaying both the buried implant 404 and the select transistor 302 active region 414. An interpoly layer 412 separates the first poly layer 410 from the second poly layer 408. The interpoly layer 412 also extends over the active region 414 and isolates the second poly layer 408 from the semiconductor substrate. The interpoly layer 412 extends continuously over the first poly layer 410 from the source dopant region 406 to the drain dopant region 402. The interpoly layer 412 may be of ONO type material. A tunnel oxide 460 of thickness 50-70 angstroms is formed in a tunnel window region between the buried implant 404 and the floating gate 410."

Please issue a Certificate of Correction, Form PTO-1050, two copies transmitted herewith.

CERTIFICATE OF MAILING

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being deposited with the United States Postal Service on the date shown below with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, Virginia 22313-1450

Signed: Brenda Elmidolan  
Typed Name: Brenda Elmidolan

Date: November 3, 2006

Respectfully submitted,

*D. M. Schneck*

David M. Schneck

Reg. No. 43,094

P.O. Box 2-E

San Jose, CA 95109-0005

(408) 297-9733

NOV - 9 2006

## UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

Page 1 of 3

PATENT NO : 6,933,557 B2  
DATED : August 23, 2005  
INVENTOR(S) : Bohumil Lojek

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 4, line 39, insert new paragraph:


With reference to Fig. 3B, the appropriate voltages for reading, erasing, and programming the blocks of the memory array 300 are managed by a memory subsystem 330. As is known to a skilled artisan, a memory controller 340 receives memory subsystem instructions and/or control signals for programming, reading, or erasing blocks or bits of a memory device such as the memory array 300. Additionally, an input/output port 350 (I/O port) receives addresses and provides appropriate voltage levels for word line, bit line, and input/output data line selection in support of memory access operations. The I/O port 350 also provides connections for communicating data with the remainder of the system 360. By selecting word lines, bit lines, and source lines and applying appropriate voltages, the controller 340 and I/O port 350 will produce reading, erasing, and programming operations.

MAILING ADDRESS OF SENDER:

Thomas Schneck  
Law Offices of Schneck & Schneck  
P.O. Box 2-E  
San Jose, CA 95109-0005

PATENT NO. 6,933,557 B2

No. of additional copies

 0

Burden Hour Statement: This form is estimated to take 1.0 hour to complete. Time will vary depending upon the needs of the individual case. Any comment on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

NOV - 9 2006

## UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

Page 2 of 3

PATENT NO : 6,933,557 B2  
DATED : August 23, 2005  
INVENTOR(S) : Bohumil Lojek

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 4, line 52 through Column 5, line 13, replace paragraphs with the following paragraphs:

With reference to Fig. 4B, a cross sectional view 400 of the memory cell 310 is illustrated. The memory cell 400 is formed on a semiconductor substrate (or well) 401 of a first conductivity type, which in the exemplary embodiment is p-type. A drain implant region 402 and a source implant region 406 are implanted within an uppermost surface of the substrate 401. A buried, heavily doped implant 404 within a portion of the floating gate region is formed essentially contiguous with the source implant region 406 within the uppermost surface of the substrate 401. The implant regions 402, 404, and 406 are of a second conductivity type of a polarity opposite that of the conductivity type of the substrate 401. In a specific exemplary embodiment, the implants are n-type. The buried implant 404 is of n+ conductivity and serves as a tunneling charge source for a floating gate of the memory transistor 400. The drain implant region 402 and the buried implant 404 are spaced apart, so as to define an active region 414 in a portion of the space therebetween. Accordingly, the drain implant region 402 connects to the bitline BL<sub>i</sub>. The source implant region 406 connects to the source line S<sub>i</sub>.

MAILING ADDRESS OF SENDER:

Thomas Schneck  
Law Offices of Schneck & Schneck  
P.O. Box 2-E  
San Jose, CA 95109-0005

PATENT NO. 6,933,557 B2

No. of additional copies

⇒ 0

Burden Hour Statement: This form is estimated to take 1.0 hour to complete. Time will vary depending upon the needs of the individual case. Any comment on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

NOV - 9 2006

## UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

Page 3 of 3

PATENT NO : 6,933,557 B2  
DATED : August 23, 2005  
INVENTOR(S) : Bohumil Lojek

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

A first poly layer 410, forming the floating gate of the memory transistor 304, overlays the buried implant region 404, separated therefrom by a gate ONO layer 450. A second poly layer 408, forming a common control gate, extends continuously over the first poly layer 410 (which forms the floating gate) from the source dopant region 406 to the drain dopant region 402, overlaying both the buried implant 404 and the select transistor 302 active region 414. An interpoly layer 412 separates the first poly layer 410 from the second poly layer 408. The interpoly layer 412 also extends over the active region 414 and isolates the second poly layer 408 from the semiconductor substrate. The interpoly layer 412 extends continuously over the first poly layer 410 from the source dopant region 406 to the drain dopant region 402. The interpoly layer 412 may be of ONO type material. A tunnel oxide 460 of thickness 50-70 angstroms is formed in a tunnel window region between the buried implant 404 and the floating gate 410.

MAILING ADDRESS OF SENDER:

Thomas Schneck  
Law Offices of Schneck & Schneck  
P.O. Box 2-E  
San Jose, CA 95109-0005

PATENT NO. 6,933,557 B2

No. of additional copies

 0

Burden Hour Statement: This form is estimated to take 1.0 hour to complete. Time will vary depending upon the needs of the individual case. Any comment on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

NOV - 9 2006

## UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

Page 1 of 3

PATENT NO : 6,933,557 B2  
DATED : August 23, 2005  
INVENTOR(S) : Bohumil Lojek

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 4, line 39, insert new paragraph:

With reference to Fig. 3B, the appropriate voltages for reading, erasing, and programming the blocks of the memory array 300 are managed by a memory subsystem 330. As is known to a skilled artisan, a memory controller 340 receives memory subsystem instructions and/or control signals for programming, reading, or erasing blocks or bits of a memory device such as the memory array 300. Additionally, an input/output port 350 (I/O port) receives addresses and provides appropriate voltage levels for word line, bit line, and input/output data line selection in support of memory access operations. The I/O port 350 also provides connections for communicating data with the remainder of the system 360. By selecting word lines, bit lines, and source lines and applying appropriate voltages, the controller 340 and I/O port 350 will produce reading, erasing, and programming operations.

MAILING ADDRESS OF SENDER:

Thomas Schneck  
Law Offices of Schneck & Schneck  
P.O. Box 2-E  
San Jose, CA 95109-0005

PATENT NO. 6,933,557 B2

No. of additional copies

⇨ 0

Burden Hour Statement: This form is estimated to take 1.0 hour to complete. Time will vary depending upon the needs of the individual case. Any comment on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

NOV - 9 2006



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.  
(Also Form PTO-1050)

## UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

Page 2 of 3

PATENT NO : 6,933,557 B2  
DATED : August 23, 2005  
INVENTOR(S) : Bohumil Lojek

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 4, line 52 through Column 5, line 13, replace paragraphs with the following paragraphs:

With reference to Fig. 4B, a cross sectional view 400 of the memory cell 310 is illustrated. The memory cell 400 is formed on a semiconductor substrate (or well) 401 of a first conductivity type, which in the exemplary embodiment is p-type. A drain implant region 402 and a source implant region 406 are implanted within an uppermost surface of the substrate 401. A buried, heavily doped implant 404 within a portion of the floating gate region is formed essentially contiguous with the source implant region 406 within the uppermost surface of the substrate 401. The implant regions 402, 404, and 406 are of a second conductivity type of a polarity opposite that of the conductivity type of the substrate 401. In a specific exemplary embodiment, the implants are n-type. The buried implant 404 is of n+ conductivity and serves as a tunneling charge source for a floating gate of the memory transistor 400. The drain implant region 402 and the buried implant 404 are spaced apart, so as to define an active region 414 in a portion of the space therebetween. Accordingly, the drain implant region 402 connects to the bitline BL<sub>i</sub>. The source implant region 406 connects to the source line S<sub>i</sub>.

MAILING ADDRESS OF SENDER:

Thomas Schneck  
Law Offices of Schneck & Schneck  
P.O. Box 2-E  
San Jose, CA 95109-0005

PATENT NO. 6,933,557 B2

No. of additional copies

⇒ 0

Burden Hour Statement: This form is estimated to take 1.0 hour to complete. Time will vary depending upon the needs of the individual case. Any comment on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

NOV - 9 2006

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.  
(Also Form PTO-1050)

## UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

Page 3 of 3

PATENT NO : 6,933,557 B2  
DATED : August 23, 2005  
INVENTOR(S) : Bohumil Lojek

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

A first poly layer 410, forming the floating gate of the memory transistor 304, overlays the buried implant region 404, separated therefrom by a gate ONO layer 450. A second poly layer 408, forming a common control gate, extends continuously over the first poly layer 410 (which forms the floating gate) from the source dopant region 406 to the drain dopant region 402, overlaying both the buried implant 404 and the select transistor 302 active region 414. An interpoly layer 412 separates the first poly layer 410 from the second poly layer 408. The interpoly layer 412 also extends over the active region 414 and isolates the second poly layer 408 from the semiconductor substrate. The interpoly layer 412 extends continuously over the first poly layer 410 from the source dopant region 406 to the drain dopant region 402. The interpoly layer 412 may be of ONO type material. A tunnel oxide 460 of thickness 50-70 angstroms is formed in a tunnel window region between the buried implant 404 and the floating gate 410.

MAILING ADDRESS OF SENDER:

Thomas Schneck  
Law Offices of Schneck & Schneck  
P.O. Box 2-E  
San Jose, CA 95109-0005

PATENT NO. 6,933,557 B2

No. of additional copies

 0

Burden Hour Statement: This form is estimated to take 1.0 hour to complete. Time will vary depending upon the needs of the individual case. Any comment on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

NOV - 9 2005